





Foster FHK Series vs. Competitive ISO B Series



Foster 1/8" to 1" FHK Series Compatible with ISO 7241-1, Series B

- 27" Hg. Maximum Rated Vacuum Pressure
- Broad Range of Metals and Seal Materials Allow the Use of Most Media
- Multiple Finish Options
- Greater Wear Resistance



Foster FHK Series	Competitive ISO B Series
<p>Radiused holes for the locking balls:</p> <ul style="list-style-type: none"> • Larger contact area (65%) • Greater wear resistance and longer life • Distributes the load while providing alignment • Swiveling action reduces hose torque and prolongs hose life  <p>Larger Contact Area Provides Greater Wear Resistance and Longer Coupling Life.</p>	<p>Tapered hole:</p> <ul style="list-style-type: none"> • Minimal ball contact • Minimum line contact decreases coupling life  <p>Minimum Line Contact Decreases Coupling Life</p>
<p>Vacuum Performance:</p> <ul style="list-style-type: none"> • Hold minimum 27" Hg for two hours with no indication of vacuum decay (test temp = 71° F) 	<p>Vacuum Performance:</p> <ul style="list-style-type: none"> • No published data
<p>Standard Spring:</p> <ul style="list-style-type: none"> • "Kick" when disconnecting from the valve springs pushes the halves apart as the valves race to their shut-off positions. 	<p>HVS Option:</p> <ul style="list-style-type: none"> • Premium purchase required for near equal performance to standard Foster product

Call ZSi-Foster at (866) 918-3003 or order now at ZSi-Foster.com

ZSi-Foster

Springfield, MO | Canton, MI | La Mirada, CA



Foster FHK Series vs. Competitive ISO B Series



Foster FHK Series	Competitive ISO B Series
1/8" Body Size in Brass Performance: <ul style="list-style-type: none"> New design provides 37% higher flow rate 	HF Option: <ul style="list-style-type: none"> Premium purchase required for near equal performance to standard Foster product
Canadian Registration Number (CRN) for the Entire Offering: <ul style="list-style-type: none"> The Canadian Registration Number (CRN) is a number issued by each province/territory of Canada to the design of pressure-containing equipment. The CRN identifies that the design has been accepted and registered for use under that province/territory Ontario = OH20062.5 • British Columbia = OH20062.51 Quebec & Saskatchewan = CSA-OH20062.56	CRN Expired as of February 10, 2018: <ul style="list-style-type: none"> Originally expired May 24, 2017 Received an extension to November 24, 2017 Received a third extension to February 10, 2018
Conical Valve Design: <ul style="list-style-type: none"> 360° metal-to-metal valve stop maintains valve alignment and ensures that poppets open fully every time 	Not Available
Multiple finish options: <ul style="list-style-type: none"> Electroless nickel Bright nickel Black zinc oxide RoHS compliant zinc clear 	Not Available
Straight Body – Benefit: <ul style="list-style-type: none"> Bodies can be threaded for bulk head mounting Valid for all material types, not just brass & SS 	Tapered Body: <ul style="list-style-type: none"> Bulk head mounting is not an option
Manufactured in an ISO 9001:2015 Certified Facility in Springfield, MO USA: <ul style="list-style-type: none"> Ensures highest product quality and standards compliance Guarantees product availability and supports fast shipment 	International sourcing with assembly in Mexico
Customer Service: <ul style="list-style-type: none"> Located in the plant of manufacture in Springfield, MO USA 	Customer Service: <ul style="list-style-type: none"> Split between Hydraulics HQ in USA and India

Call ZSi-Foster at (866) 918-3003 or order now at ZSi-Foster.com

ZSi-Foster

Springfield, MO | Canton, MI | La Mirada, CA