
Installation and Instruction Sheets

TBC & TBC C - T-BAR CLIP AND T-BAR CLIP WITH CONDUIT CLIP

SHEET: 1 OF 2



Catalog Number	HS-1	HS-2	Conduit Size
TBC1	1/4" x 20 Thread Form	7/32"	N/A
TBC2	1/4" x 20 Thread Form	7/32"	N/A
TBC1C812	N/A	7/32"	1/2" EMT, IMC, Rigid 3/4" EMT, IMC, Rigid
TBC1C16	N/A	7/32"	1" EMT, Rigid
TBC2C812	N/A	7/32"	1/2" EMT, IMC, Rigid 3/4" EMT, IMC, Rigid
TBC2C16	N/A	7/32"	1" EMT, Rigid



Notes

- May require dedicated drop wire(s) check local authority.
- For support of conduit per NEC 344.30(B).

Warning: Do not use for hanging tee-grid system.


Revision: 0




Call ZSi-Foster at (800) 323-7053 or order now at ZSi-Foster.com

CUSTOMER RESPONSIBILITIES: At a minimum the customer(s) is responsible for using industry standard hardware and fasteners, inspecting the structural integrity of the structure to which ZSi-Foster products will be attached, conforming to all governing codes and regulations at the job site and following all safety precautions related to the work being performed.

WARNING: ZSi-Foster products must never be used for purposes other than those for which they were designed or in any way that exceeds published load ratings. All load ratings are for static conditions and do not account for dynamic loading such as wind, water or seismic loads. ZSi-Foster products must be installed and used only as indicated in ZSi-Foster installation and instruction sheets. Improper installation, misuse, misapplication or any other failure to completely follow ZSi-Foster's instructions could lead to decreased load rating, product failure, property damage, injury or even death.





Call ZSi-Foster at (800) 323-7053 or order now at ZSi-Foster.com